# NATIONAL BUREAU OF STANDARDS REPORT

10 038

## MISCELLANEOUS STRUCTURAL COMPUTER PROGRAMS

Modified for IBM 1130

for: The Construction Research Division
Post Office Department

U.S. DEPARTMENT OF COMMERCE
NATIONAL BUREAU OF STANDARDS

## NATIONAL BUREAU OF STANDARDS

The National Bureau of Standards[1] was established by an act of Congress March 3, 1901. Today, in addition to serving as the Nation's central measurement laboratory, the Bureau is a principal focal point in the Federal Government for assuring maximum application of the physical and engineering sciences to the advancement of technology in industry and commerce. To this end the Bureau conducts research and provides central national services in three broad program areas and provides central national services in a fourth. These are: (1) basic measurements and standards, (2) materials measurements and standards, (3) technological measurements and standards, and (4) transfer of technology.

The Bureau comprises the Institute for Basic Standards, the Institute for Materials Research, the Institute for Applied Technology, and the Center for Radiation Research.

**THE INSTITUTE FOR BASIC STANDARDS** provides the central basis within the United States of a complete and consistent system of physical measurement, coordinates that system with the measurement systems of other nations, and furnishes essential services leading to accurate and uniform physical measurements throughout the Nation's scientific community, industry, and commerce. The Institute consists of an Office of Standard Reference Data and a group of divisions organized by the following areas of science and engineering:

Applied Mathematics—Electricity—Metrology—Mechanics—Heat—Atomic Physics—Cryogenics[2]—Radio Physics[2]—Radio Engineering[2]—Astrophysics[2]—Time and Frequency.[2]

**THE INSTITUTE FOR MATERIALS RESEARCH** conducts materials research leading to methods, standards of measurement, and data needed by industry, commerce, educational institutions, and government. The Institute also provides advisory and research services to other government agencies. The Institute consists of an Office of Standard Reference Materials and a group of divisions organized by the following areas of materials research:

Analytical Chemistry—Polymers—Metallurgy — Inorganic Materials — Physical Chemistry.

**THE INSTITUTE FOR APPLIED TECHNOLOGY** provides for the creation of appropriate opportunities for the use and application of technology within the Federal Government and within the civilian sector of American industry. The primary functions of the Institute may be broadly classified as programs relating to technological measurements and standards and techniques for the transfer of technology. The Institute consists of a Clearinghouse for Scientific and Technical Information,[3] a Center for Computer Sciences and Technology, and a group of technical divisions and offices organized by the following fields of technology:

Building Research—Electronic Instrumentation — Technical Analysis — Product Evaluation—Invention and Innovation— Weights and Measures — Engineering Standards—Vehicle Systems Research.

**THE CENTER FOR RADIATION RESEARCH** engages in research, measurement, and application of radiation to the solution of Bureau mission problems and the problems of other agencies and institutions. The Center for Radiation Research consists of the following divisions:

Reactor Radiation—Linac Radiation—Applied Radiation—Nuclear Radiation.

---

[1] Headquarters and Laboratories at Gaithersburg, Maryland, unless otherwise noted; mailing address Washington, D. C. 20234.
[2] Located at Boulder, Colorado 80302.
[3] Located at 5285 Port Royal Road, Springfield, Virginia 22151.

# NATIONAL BUREAU OF STANDARDS REPORT

**NBS PROJECT**
4213417

**NBS REPORT**
10 038

## MISCELLANEOUS STRUCTURAL COMPUTER PROGRAMS

Modified for IBM 1130
by
E. F. Carpenter

for: The Construction Research Division
Post Office Department

IMPORTANT NOTICE

NATIONAL BUREAU OF STAN
for use within the Government. Be
and review. For this reason, the p
whole or in part, is not authorize
Bureau of Standards, Washington,
the Report has been specifically pr

Approved for public release by the director of the National Institute of Standards and Technology (NIST) on October 9, 2015

accounting documents intended
bjected to additional evaluation
sting of this Report, either in
Office of the Director, National
the Government agency for which
ies for its own use.

U.S. DEPARTMENT OF COMMERCE
NATIONAL BUREAU OF STANDARDS

TABLE OF CONTENTS

1. Introduction ---------- 1

2. Program 2.A.1 - Deflection of Cantilever Beam--------- 3

3. Program 2.A.2 - Deflection of Continuous Beam
With Uniform Load ---------- 5

4. Program 2.A.3 - Fixed-End Beam Deflections ----------7

5. Program 2.B.1 - Concrete Frame Analysis (Part I) ----- 9

6. Program 2.B.2 - Concrete Frame Analysis (Part II)-----13

7. Program 2.B.3 - Concrete Frame Analysis (Part III)----15

8. Summary ---------- 17

SAMPLE INPUT FORMS

PROGRAM LISTS WITH SAMPLE OUTPUT

ACKNOWLEDGEMENT

# 1. INTRODUCTION

## 1.1. General

This is the second of two reports designed to modify, consolidate, and coordinate certain existing structural computer programs, to make them compatible with current building codes and the IBM 1130/FORTRAN IV language. This report is intended as a reference manual for the structural engineering use of six-beam deflection and concrete-frame programs.

The following programs are included:

(1) Deflection of Cantilevered Beams;

(2) Deflection of a Continuous Beam with Uniform Loads;

(3) Deflection of Fixed-End Beams;

(4) Concrete Frame Analysis, including conduits, culverts, three-story frame analysis, up to seven-span continuous beams. (Three programs)

The original computer programs were written in various FORTRAN forms, including RCA 301/FORTRAN, and IBM 1620/FORTRAN. These have all been modified to IBM 1130/FORTRAN, operable with the following equipment:

(a) IBM 1130, Model 2C, 16-K Storage/Version II;

(b) IBM 1132 Printer

(c) IBM Card Read-Punch;

(d) IBM 2315 Disc Cartridge, Removable/Interchangeable.

## 1.2. Scope

Each program has been checked for building code references, and modified where necessary to meet ACI 318-63, or AISC-63 specifications.

Programs have been debugged by performing an illustrative problem. No comprehensive full-scale attempt has been made to check against manual solutions and establish analytical validity. The user must satisfy himself as to reliability by testing the program with problems of known solution. Good engineering practice dictates that each program be used initially as a checking analysis until the user gains sufficient confidence and insight into the program's behavior. The theoretical basis and program abstracts described in Sections 2 thru 7 are presented to provide the user a quick reference as to the general nature of the program. Several of these programs, notably 2.B.1, 2.B.2, and 2.B.3, have been previously documented in considerable detail. If further information is required, reference can be made to that documentation.

A standard description sheet of each program is included in the Summary, to provide a consolidated definition of the program.

# 2. PROGRAM 2.A.1 - FIXED-END BEAM DEFLECTION

## 2.1. Purpose

The purpose of Program 2.A.1 is to calculate the deflection and slope at the end of a cantilever. The cantilever can be of varying cross-section. The applied loads consist of the uniform load over the entire beam and/or a point load at the end.

## 2.2. Theoretical Basis

Analytical calculations are based on the conjugate beam theory, combined with a numerical incrementing procedure that requires the beam to be subdivided into nine segments.

## 2.3. Input

The input consists of the beam dimensions and load factors on punched cards. Since there are nine segments, there will be ten points at which the moment of inertia and point location must be specified. Within the program, these points are numbered #1 through #10, beginning at the point nearest the fixed end. As can be seen below, cards 2(a) and (b), and cards 3(a) and (b) provide the point information. If it were desirable to use fewer than ten points, say one point to represent a uniform beam of uniform cross-section, one would need only enter the

pertinent information in the first field of card 2(a) and 3(a), leaving the remaining fields of card 2(a), 2(b), 3(a), 3(b) blank. Input parameters are read by the computer in the following sequence:

Card 1
- SPAN - length of beam in feet
- UDL - uniformly distributed load (kips per lineal foot)
- XP - distance from the concentrated load to the fixed end in feet
- P - applied concentrated load in kips
- E - modulus of elasticity (KSI)

Card 2 (a) and (b)
- XI(1 through 10) - these are the moments of inertia at the various points (inches to the fourth power)

Card 3 (a) and (b)
- SL (1 through 10) - these two cards contain the distances of the points from the fixed end (feet)

## 2.4. Output

Output information includes the following:

A listing of the input data.

Slope and deflection for the free end of the cantilever are printed, deflection being in inches.

The input and output features of this program can be easily modified by an individual familiar with FORTRAN, to provide a job-stacking capability, or more comprehensive input-output formatting procedures.

# 3. PROGRAM 2.A.2 - CONTINUOUS BEAM DEFLECTIONS

## 3.1. Purpose

The purpose of this program is to calculate the deflections at any desired spacing along the length of a uniformly loaded beam, having a constant moment of inertia, and given the moments at the supports.

## 3.2. Theoretical Basis

The conjugate-beam method is used in the manner described in an article appearing in the September 1961 issue of Civil Engineering, entitled "Deflection Calculated by the Conjugate-Beam Method," written by Jack I. Mann.

The conjugate beam is constructed by loading a simple beam with the M/EI diagram of the real beam. The reactions of the conjugate beam represent the slopes on the ends of the real beam, and, since the supports of the real beam are assumed not to deflect, there is no moment at the end of the conjugate beam. The basic design equation is:

## 3.3. Input

Input is very simple and requires only one card per beam.

This card has seven parameters, which are as follows:

Card 1

AL - length of beam in feet
SM - simple beam moment in kip-ft.
AM - moment at support A in kip-ft.
BM - moment at support B in kip-ft.
E - modulus of elasticity in KSI
AI - moment of inertia in inches to the fourth power
ZNUM - percentage of span indicating points at which deflection is to be computed (i.e., .1 would be 1/10 points)

## 3.4. Output

Output is simply two columns of numbers, the first column being the distance from end A, and the second column being deflection at that point in inches.

PROGRAM 2.A.3 - DEFLECTION OF FIXED-END BEAMS

## 4.1. Purpose

This program computes the deflections at tenth points of a beam with both ends fixed, and with one end fixed and one end free.

## 4.2. Theoretical Basis

The formula used to calculate deflections of the beam with both ends fixed is as follows:

$$\Delta x = \frac{w x^2}{24 E I} (L - x)^2$$

The formula used to calculate deflections for a beam with one end fixed and one end free is as follows:

$$\Delta x = \frac{w x}{48 E I} (L^3 - 3 L x^2 + 2 x^3)$$

## 4.3. Input

The input for this program consists of one card per beam. The card contains the following parameters:

Card 1
- AL - length of span in feet
- E - modulus of elasticity in KSI
- AI - moment of inertia in inches to the fourth power
- W - uniform load in kips per foot

## 4.4. Output

The output consists of three columns, the first being the location of the deflection relative to the left end, or free end for the unsymmetrical beam. The second column gives the deflection for the beam with both ends fixed. The third column gives the deflection in inches for the beam with one end free.

This program can be used for more than one beam at a time and serves as a convenient method to compare the effects of fixity on deflection.

# 5. PROGRAM 2.B.1 - CONCRETE FRAME ANALYSIS - PART I

## 5.1. Purpose

This program provides an analysis of reinforced concrete structures, including concrete conduits or culverts under high fill. The program is limited to the analysis of uniformly loaded haunched-end or prismatic members which are not subjected to conditions of side-sway. However, assumed side-sway moment distribution can be accomplished separately with the program, and the results combined manually. The program has been divided into three parts, this first part of which computes fixed-end moments, distribution factors, carry-over factors, distributed moments, and that point on the member where the moment of inertia is no longer assumed equal to infinity. Part I also produces the punched data deck for input to the second part (2.B.2).

## 5.2. Theoretical Basis

The conduit analysis assumes a rectangular or box shape for the exterior of the structure, with either square or simulated-round interior barrels. The simulated-round barrel is represented by an octagonal cross-section, thus utilizing a haunched-member assumption.

The basic situation is a three-celled structure with each member represented by dual numbers. This numerical designation for the numbers is necessarily applied to all situations, and for each situation, twenty sets of input data must be entered. The values entered typify the particular structure being analyzed. For prismatic members, the input format is filled by entering zeros in the positions allocated to length of haunch and slope of haunch. By entering zeros exclusively in the positions allocated to loading, and by entering zeros or ones in the positions designated for moments of inertia, certain members are virtually eliminated from consideration, thus providing for the analysis of a variety of structures.

## 5.3. Input

Only one type of input card is required; however, twenty of these cards are used for every problem. Each of the twenty cards provides the data for the twenty positions shown in the following figure:

Each of the twenty cards requires numeration of the following parameters:

Card 1
- S - the 20 numbers in the figure above can be thought of as beam ends. S is the span length of the beam associated with each particular number.
- SK - this is the thickness of each member in feet
- COF - this is the haunched depth in feet (if any)
- AI - this is the relative moment of inertia
- DM - slope of the haunch
- W - uniform load in kips per foot
- BAL - depth to center of steel from tensile face in feet

It should be remembered that the program expects to find three cells consisting of twenty members. In the event that fewer cells or members are desired, the programmer should insert artificial members that have negligable effect on the analysis: i.e., small moment of inertia, small thickness, and small uniform load.

## 5.4. Output

This first phase of the concrete frame program computes fixed-end moments, distribution factors, carry-over factors, distributed moments, and that point on the member where the moment of inertia is no longer assumed equal to infinity. The output from this first phase consists of a set of punched cards for input to the second program, 2.B.2, and printed results of five factors for each member. These factors are as follows:

FEM - Fixed-end moments in kip-ft.;

A - Flexibility coefficient times length;

DF - Distribution factor;

COF - Haunch depth in feet;

DM - Distributed moment in kip-ft.

## 6. PROGRAM 2.B.2 - CONCRETE FRAME ANALYSIS - Part II

### 6.1. Purpose

The objective of this second phase of the three-part program is to compute values of shear and unit shear at various points along the members, and to produce punched data for input to the third part. The theoretical basis is as described in Program 2.B.1.

### 6.2. Input and Output

The input for this phase of the program consists of the forty cards prepared by 2.B.1. The first twenty of these cards each contain six numbers representing the various programming coefficients. The second set of twenty cards each contains three coefficients.

The output of Program 2.B.2 can be varied by using Switch 1 and Switch 2. The normal output with both switches off consists of the following:

V - this is the end-sheer in kips;

VA - shear at point of infinite I in kips;

VAEH - this is the change in shear from location of VA to the end of the haunch;

VEH - shear at the end of the haunch in kips;

VPC - shear at the point of counter-flexture in kips;

USA - unit shear for VA in KSI;

USAEH - unit shear for VAEH in KSI;

USEH - unit shear for VEH in KSI;

USPC - unit sheer for VPC in KSI.

In addition to the printed output, this program punches cards for input to the third phase of the system.

# 7. PROGRAM 2.B.3 - CONCRETE FRAME ANALYSIS - Part III

## 7.1. Purpose

Program 2.B.3 is the third part of a three-step analysis of concrete frames or rings, such as culverts and tunnels. This part computes the distance to various points along the members, together with the respective moments found at these positions. A moment correction factor is also computed. This can be used, if necessary, in accordance with the description contained in "Continuity in Concrete Building Frames," Fourth edition, Portland Cement Association.

## 7.2. Input-Output

The input of Program 2.B.3 consists of forty cards punched by Program 2.B.2. The first twenty cards contain eight coefficients. The second twenty each contain five coefficients.

The output with Data Switch 1 off, consists of the following:

S - span length in feet;

XF - distance to face of member in feet;

A - distance to infinite inertia in feet;

XEH - distance to end of haunch in feet;

XMVER - distance to point of counter-flecture in feet;

XMPOS - distance to maximum positive moment in feet;

DM, DMF, DMA, DMEH, DMPOS - these are the moments in kip-ft. at the positions indicated above, the face, the point of infinite inertia, the end of haunch, and the maximum positive moment;

DMCOR - this is the moment distribution correction factor previously referenced.

SUMMARY SHEET FOR PROGRAM NO. 2.A.1

PROGRAM NAME:

Deflection of Cantilever Beams

A. TYPE OF MATERIAL

| | |
|---|---|
| x | 1. Concrete |
| x | 2. Steel |

B. TYPE OF STRUCTURE

| | |
|---|---|
| x | 1. Beams and Girders |
| | 2. Columns |
| | 3. Composite Beams |
| | 4. Foundations |
| | 5. Frames and Tunnels |
| | 6. Prestress Construction |
| | 7. Shells |
| | 8. Slabs |

C. REFERENCE CODES

| | |
|---|---|
| N/A | 1. A.C.I. |
| | 2. A.I.S.C. |
| | 3. A.A.S.H.O. |

D. TYPE OF ANALYSIS

| | |
|---|---|
| x | 1. Elastic Analysis |
| | 2. Plastic Analysis |
| | 3. Working Strength Design |
| | 4. Ultimate Strength Design |

E. REMARKS

SUMMARY SHEET FOR PROGRAM NO. 2.A.2

PROGRAM NAME: Deflection of Continuous Beams With Uniform Load

A. TYPE OF MATERIAL

| | |
|---|---|
| x | 1. Concrete |
| x | 2. Steel |

B. TYPE OF STRUCTURE

| | |
|---|---|
| x | 1. Beams and Girders |
| ___ | 2. Columns |
| ___ | 3. Composite Beams |
| ___ | 4. Foundations |
| ___ | 5. Frames and Tunnels |
| ___ | 6. Prestress Construction |
| ___ | 7. Shells |
| ___ | 8. Slabs |

C. REFERENCE CODES

| | |
|---|---|
| N/A | 1. A.C.I. |
| ___ | 2. A.I.S.C. |
| ___ | 3. A.A.S.H.O. |

D. TYPE OF ANALYSIS

| | |
|---|---|
| x | 1. Elastic Analysis |
| ___ | 2. Plastic Analysis |
| ___ | 3. Working Strength Design |
| ___ | 4. Ultimate Strength Design |

E. REMARKS

SUMMARY SHEET FOR PROGRAM NO. 2.A.3

PROGRAM NAME: Fixed-End Beam Deflections

A. TYPE OF MATERIAL

| | |
|---|---|
| x | 1. Concrete |
| x | 2. Steel |

B. TYPE OF STRUCTURE

| | |
|---|---|
| x | 1. Beams and Girders |
| ____ | 2. Columns |
| ____ | 3. Composite Beams |
| ____ | 4. Foundations |
| ____ | 5. Frames and Tunnels |
| ____ | 6. Prestress Construction |
| ____ | 7. Shells |
| ____ | 8. Slabs |

C. REFERENCE CODES

| | |
|---|---|
| N/A | 1. A.C.I. |
| ____ | 2. A.I.S.C. |
| ____ | 3. A.A.S.H.O. |

D. TYPE OF ANALYSIS

| | |
|---|---|
| x | 1. Elastic Analysis |
| ____ | 2. Plastic Analysis |
| ____ | 3. Working Strength Design |
| ____ | 4. Ultimate Strength Design |

E. REMARKS

SUMMARY SHEET FOR PROGRAM NO. 2.B.1

PROGRAM NAME:

Concrete Frame Analysis (Part I)

A. TYPE OF MATERIAL

| | |
|---|---|
| x | 1. Concrete |
| | 2. Steel |

B. TYPE OF STRUCTURE

| | |
|---|---|
| | 1. Beams and Girders |
| | 2. Columns |
| | 3. Composite Beams |
| | 4. Foundations |
| x | 5. Frames and Tunnels |
| | 6. Prestress Construction |
| | 7. Shells |
| | 8. Slabs |

C. REFERENCE CODES

| | |
|---|---|
| x | 1. A.C.I. |
| | 2. A.I.S.C. |
| | 3. A.A.S.H.O. |

D. TYPE OF ANALYSIS

| | |
|---|---|
| x | 1. Elastic Analysis |
| | 2. Plastic Analysis |
| | 3. Working Strength Design |
| | 4. Ultimate Strength Design |

E. REMARKS

Particularly well suited to tunnel design.

SUMMARY SHEET FOR PROGRAM NO. 2.B.2

PROGRAM NAME:

Concrete Frame Analysis (Part II)

A. TYPE OF MATERIAL

| | |
|---|---|
| x | 1. Concrete |
| | 2. Steel |

B. TYPE OF STRUCTURE

| | |
|---|---|
| | 1. Beams and Girders |
| | 2. Columns |
| | 3. Composite Beams |
| | 4. Foundations |
| x | 5. Frames and Tunnels |
| | 6. Prestress Construction |
| | 7. Shells |
| | 8. Slabs |

C. REFERENCE CODES

| | |
|---|---|
| x | 1. A.C.I. |
| | 2. A.I.S.C. |
| | 3. A.A.S.H.O. |

D. TYPE OF ANALYSIS

| | |
|---|---|
| x | 1. Elastic Analysis |
| | 2. Plastic Analysis |
| | 3. Working Strength Design |
| | 4. Ultimate Strength Design |

E. REMARKS

Requires input from 2.B.1

SUMMARY SHEET FOR PROGRAM NO. 2.B.3

PROGRAM NAME: Concrete Frame Analysis (Part III)

A. TYPE OF MATERIAL

- [x] 1. Concrete
- [ ] 2. Steel

B. TYPE OF STRUCTURE

- [ ] 1. Beams and Girders
- [ ] 2. Columns
- [ ] 3. Composite Beams
- [ ] 4. Foundations
- [x] 5. Frames and Tunnels
- [ ] 6. Prestress Construction
- [ ] 7. Shells
- [ ] 8. Slabs

C. REFERENCE CODES

- [x] 1. A.C.I.
- [ ] 2. A.I.S.C.
- [ ] 3. A.A.S.H.O.

D. TYPE OF ANALYSIS

- [x] 1. Elastic Analysis
- [ ] 2. Plastic Analysis
- [ ] 3. Working Strength Design
- [ ] 4. Ultimate Strength Design

E. REMARKS

Requires input from 2.B.2

IBM

# FORTRAN CODING FORM

Program 2.A.1
Coded By E.F.C.
Checked By

Identification (73–80)

Date MAY 9/69
Page 1 of 1

C FOR COMMENT

| STATEMENT NUMBER (1–5) | Cont. (6) | FORTRAN STATEMENT (7–72) |
|---|---|---|
| 20. | | 10. 0. 0. 30000. |
| 14928. | | |
| 20. | | |

IBM

# FORTRAN CODING FORM

Printed in U.S.A

Program 2.A.2
Coded By ESC
Checked By

Identification
73 80

Date MAY 9/69
Page 1 of 1

C FOR COMMENT

| STATEMENT NUMBER (1–5) | Cont. (6) | FORTRAN STATEMENT (7–72) |
|---|---|---|
| 0140. | 0 | 0028170.-0101922.-0011922. 30.0E 03 11.0E 05.10 |

IBM

# FORTRAN CODING FORM

Program 2.A.3
Coded By ESC
Checked By

Identification
73 80

Date May 9/69
Page 1 of 1

C FOR COMMENT

| STATEMENT NUMBER 1 5 | Cont. 6 | FORTRAN STATEMENT 7 10 15 20 25 30 35 40 45 50 55 60 65 70 7 |
|---|---|---|
| 40. | | 30000,000. 14988. 833. |

IBM

# FORTRAN CODING FORM

Form X25 7327
Printed in U.S.A.

Program 2.B.1
Coded By E F C
Checked By

Identification (73–80)

Date May 6/69
Page 1 of 1

C FOR COMMENT

| STATEMENT NUMBER (1–5) | Cont. (6) | FORTRAN STATEMENT (7–72) | |
|---|---|---|---|
| | | 0 9 . 5 0 0 4 . 7 5 0 2 . 7 8 2 5 0 1 . 0 0 1 . 0 0 0 0 4 0 . 2 0 0 . 3 3 3 | CARD # 1 |
| | | 0 9 . 5 0 0 4 . 7 5 0 2 . 7 8 2 5 0 1 . 0 0 1 . 0 0 0 0 - 4 0 . 2 0 0 . 3 3 3 | CARD # 2 |
| | | | SAME AS CARD # 1 |
| | | | SAME AS CARD # 2 |
| | | | SAME AS CARD # 1 |
| | | | SAME AS CARD # 2 |
| | | 0 9 . 5 0 0 4 . 7 5 0 2 . 7 8 2 5 0 1 . 0 0 1 . 0 0 0 0 1 3 . 4 0 0 . 3 3 3 | CARD # 3 |
| | | 0 9 . 5 0 0 4 . 7 5 0 2 . 7 8 2 5 0 1 . 0 0 1 . 0 0 0 0 - 1 3 . 4 0 0 . 3 3 3 | CARD # 4 |
| | | | SAME AS CARD # 1 |
| | | | SAME AS CARD # 2 |
| | | | SAME AS CARD # 1 |
| | | | SAME AS CARD # 2 |
| | | | SAME AS CARD # 1 |
| | | | SAME AS CARD # 2 |
| | | | SAME AS CARD # 3 |
| | | | SAME AS CARD # 4 |
| | | 0 9 . 5 0 0 4 . 7 5 0 2 . 7 8 2 5 0 1 . 0 0 1 . 0 0 0 0 0 0 . 0 0 0 . 3 3 3 | CARD # 5 |
| | | | SAME AS CARD # 5 |
| | | | SAME AS CARD # 5 |
| | | | SAME AS CARD # 5 |

LISTING AND SAMPLE OUTPUT

for

PROGRAM 2.A.1. - DEFLECTION OF CANTILEVER

```
// JOB 1
// FOR
*IOCS(CARD,1132PRINTER,DISK)
*LIST ALL
C       CANTILEVER DEFLECTION PROGRAM                                          2A1
        DIMENSION XI(10), XL(10), DE(211), XXI(211), XM(211), SLOPE(211)       2A1
        DIMENSION DEFL(211)                                                    2A1
1       CONTINUE                                                               2A1
        WRITE (3,35)                                                           2A1
        WRITE (3,36)                                                           2A1
        READ (2,34) SPAN,UDL,XP,P,E                                            2A1
        WRITE (3,38)                                                           2A1
        WRITE (3,35)                                                           2A1
        WRITE (3,36)                                                           2A1
        WRITE (3,34) SPAN,UDL,XP,P,E                                           2A1
        WRITE (3,36)                                                           2A1
        WRITE (3,37)                                                           2A1
        READ (2,34) XI(1),XI(2),XI(3),XI(4),XI(5)                              2A1
        READ (2,34) XI(6),XI(7),XI(8),XI(9),XI(10)                             2A1
        WRITE (3,34) XI(1),XI(2),XI(3),XI(4),XI(5)                             2A1
        WRITE (3,34) XI(6),XI(7),XI(8),XI(9),XI(10)                            2A1
        WRITE (3,36)                                                           2A1
        WRITE (3,40)                                                           2A1
        READ (2,34) XL(1),XL(2),XL(3),XL(4),XL(5)                              2A1
        READ (2,34) XL(6),XL(7),XL(8),XL(9),XL(10)                             2A1
        WRITE (3,34) XL(1),XL(2),XL(3),XL(4),XL(5)                             2A1
        WRITE (3,34) XL(6),XL(7),XL(8),XL(9),XL(10)                            2A1
        WRITE (3,36)                                                           2A1
        SPAN=SPAN*12.0                                                         2A1
        UDL=UDL*1000.0/12.0                                                    2A1
        XP=XP*12.0                                                             2A1
        P=P*1000.0                                                             2A1
        E=E*1000.0                                                             2A1
        DO 2 N=1,10                                                            2A1
2       XL(N)=XL(N)*12.0                                                       2A1
        AL=SPAN/200.0                                                          2A1
C       DE = DISTANCE FROM END OF CANTILEVER                                   2A1
        Z=XL(10)+XL(9)+XL(8)+XL(7)+XL(6)+XL(5)                                 2A1
        DO 25 N=1,200                                                          2A1
        IF (N-1) 3,3,4                                                         2A1
3       DE(N)=AL*0.5                                                           2A1
        GO TO 5                                                                2A1
4       K=N-1                                                                  2A1
        DE(N)=DE(K)+AL                                                         2A1
5       CONTINUE                                                               2A1
        IF (DE(N)-XL(10)) 6,6,7                                                2A1
6       XXI(N)=XI(10)                                                          2A1
        GO TO 24                                                               2A1
7       IF (DE(N)-XL(10)-XL(9)) 8,8,9                                          2A1
8       XXI(N)=XI(9)                                                           2A1
        GO TO 24                                                               2A1
9       IF (DE(N)-XL(10)-XL(9)-XL(8)) 10,10,11                                 2A1
10      XXI(N)=XI(8)                                                           2A1
        GO TO 24                                                               2A1
11      IF (DE(N)-XL(10)-XL(9)-XL(8)-XL(7)) 12,12,13                           2A1
12      XXI(N)=XI(7)                                                           2A1
        GO TO 24                                                               2A1
13      IF (DE(N)-XL(10)-XL(9)-XL(8)-XL(7)-XL(6)) 14,15,15                     2A1
14      XXI(N)=XI(6)                                                           2A1
        GO TO 24                                                               2A1
15      IF (DE(N)-XL(10)-XL(9)-XL(8)-XL(7)-XL(6)-XL(5)) 16,17,17               2A1
16      XXI(N)=XI(5)                                                           2A1
```

```
      GO TO 24                                                          2A1
17    IF (DE(N)-Z-XL(4)) 18,19,19                                       2A1
18    XXI(N)=XI(4)                                                      2A1
      GO TO 24                                                          2A1
19    IF (DE(N)-Z-XL(4)-XL(3)) 20,20,21                                 2A1
20    XXI(N)=XI(3)                                                      2A1
      GO TO 24                                                          2A1
21    IF (DE(N)-Z-XL(4)-XL(3)-XL(2)) 22,22,23                           2A1
22    XXI(N)=XI(2)                                                      2A1
      GO TO 24                                                          2A1
23    XXI(N)=XI(1)                                                      2A1
24    CONTINUE                                                          2A1
25    CONTINUE                                                          2A1
      DO 28 N=1,200                                                     2A1
      XM(N)=DE(N)*DDL*DE(N)*0.5                                         2A1
      IF (DE(N)+XP-SPAN) 27,27,26                                       2A1
26    XM(N)=XM(N)+(DE(N)+XP-SPAN)*P                                     2A1
27    CONTINUE                                                          2A1
28    CONTINUE                                                          2A1
      DO 32 N=1,200                                                     2A1
      IF (N-1) 29,29,30                                                 2A1
29    SLOPE(N)=AL*XM(N)/(E*XXI(N))                                      2A1
      DEFL(N)=AL*XM(N)*DE(N)/(E*XXI(N))                                 2A1
      GO TO 31                                                          2A1
30    L=N-1                                                             2A1
      SLOPE(N)=SLOPE(L)+(AL*XM(N)/(E*XXI(N)))                           2A1
      DEFL(N)=DEFL(L)+(AL*XM(N)*DE(N)/(E*XXI(N)))                       2A1
31    CONTINUE                                                          2A1
32    CONTINUE                                                          2A1
      WRITE (3,38)                                                      2A1
      WRITE (3,41)                                                      2A1
      WRITE (3,38)                                                      2A1
      WRITE (3,38)                                                      2A1
      WRITE (3,43)                                                      2A1
      WRITE (3,42) SLOPE(200),DEFL(200)                                 2A1
      WRITE (3,39)                                                      2A1
      GO TO 1                                                           2A1
C                                                                       2A1
33    FORMAT (18X,21HCANTILEVER DEFLECTION)                             2A1
34    FORMAT (1X,6F12.3)                                                2A1
35    FORMAT (6X,4HSPAN,9X,3HDDL,9X,2HXP,10X,1HP,12X,1HE)               2A1
36    FORMAT (7X,2HFT,10X,4HK/FT,8X,4HFEET,8X,4HKIPS,8X,3HKSI)          2A1
37    FORMAT (7X,49HMOMENTS OF INERTIA (IN**4) FROM FIXED TO FREE END)  2A1
38    FORMAT (1H )                                                      2A1
39    FORMAT (1H1)                                                      2A1
40    FORMAT (7X,52HLENGTH OF CONSTANT I SEGMENTS FROM FIXED TO FREE END2A1
     1)                                                                 2A1
41    FORMAT (18X,10HOUTPUT     )                                       2A1
42    FORMAT (13X,F10.8,8X,F16.8)                                       2A1
43    FORMAT (18X,5HSLOPE,19X,10HDEFLECTION)                            2A1
      END)                                                              2A1
// DUP
*STORE       WS  UA  M2A1
// XQT M2A1
```

CANTILEVER DEFLECTION

| SPAN | UDL | XP | P | E |
|---|---|---|---|---|
| FT | K/FT | FEET | KIPS | KSI |
| 20.000 | 10.000 | .000 | .000 | 30000.000 |

MOMENTS OF INERTIA (FT**4) FROM FIXED TO FREE END

| | | | | |
|---|---|---|---|---|
| 14988.000 | .000 | .000 | .000 | .000 |
| .000 | .000 | .000 | .000 | .000 |

LENGTH OF CONSTANT I SEGMENTS FROM FIXED TO FREE END

| | | | | |
|---|---|---|---|---|
| 20.000 | .000 | .000 | .000 | .000 |
| .000 | .000 | .000 | .000 | .000 |

OUTPUT

| SLOPE | DEFLECTION |
|---|---|
| .00427005 | .76860419 |

LISTING AND SAMPLE OUTPUT

for

PROGRAM 2.A.2 - DEFLECTION OF CONTINUOUS BEAM

```
// JOB T
// FOR
*IOCS(CARD,1132PRINTER,DISK)
*LIST ALL
C     POD STRUCTURAL PROGRAM SCD-7                                          2A2
C     DEFLECTION BY CONJUGATE-BEAM METHOD                                   2A2
1     READ (2,4) AL,SM,AM,BM,E,AI,ZNUM                                      2A2
      X=ZNUM*AL                                                             2A2
      Y=ZNUM                                                                2A2
      WRITE (3,5)                                                           2A2
2     A=Y**2                                                                2A2
      B=Y**3                                                                2A2
      C=Y**4                                                                2A2
      D=Y**5                                                                2A2
      SK=556.15*Y+94.29*A-1299.04*B+646.41*C+2.23*D                         2A2
      AK=497.31*Y-336.54*A-967.65*B+1277.11*C-470.01*D                      2A2
      BK=320.01*Y-271.69*A+543.99*B-1055.24*C+462.97*D                      2A2
      DEF=(AL**2/(E*AI))*(SM*SK+AM*AK+BM*BK)                                2A2
      WRITE (3,6) X,DEF                                                     2A2
      Y=Y+ZNUM                                                              2A2
      X=X+(ZNUM*AL)                                                         2A2
      IF (X-AL) 2,3,3                                                       2A2
3     CONTINUE                                                              2A2
C                                                                           2A2
4     FORMAT (F5.0,F8.0,F8.0,F8.0,F8.0,E9.1,E8.1,F3.2)                      2A2
5     FORMAT (1H1,'DISTDEFL(INS)')                                          2A2
6     FORMAT (F7.2,F8.4)                                                    2A2
      END                                                                   2A2
// DUP
*STORE       WS  UA  M2A2
// XQT M2A2
```

| [illegible] | [illegible] |
|---|---|
| 14.00 | .0924 |
| 28.00 | .2719 |
| 42.00 | .4586 |
| 56.00 | .5956 |
| 70.00 | .6421 |
| 84.00 | .5954 |
| 98.00 | .4585 |
| 112.00 | .2716 |
| 126.00 | .0914 |
| 140.00 | -.0004 |

LISTING AND SAMPLE OUTPUT

FOR PROGRAM 2.A.3

FIXED-END BEAM DEFLECTIONS

```
// JOB T
// FOR
*IOCS(CARD,1132PRINTER,DISK)
*LIST ALL
C       STRUCTURAL PROGRAM SCP=8                                        2A3
C       DEFLECTION AT TENTH-POINTS OF A FIXED-END BEAM                  2A3
1       READ (2,6) AL,E,AI,W                                            2A3
        AL=12.*AL                                                       2A3
        X=.1*AL                                                         2A3
        WRITE (3,7)                                                     2A3
        WRITE (3,8)                                                     2A3
2       A=X**2.                                                         2A3
        B=W*A                                                           2A3
        C=B/24.                                                         2A3
        D=C/E                                                           2A3
        F=D/AI                                                          2A3
        Q=AL-X                                                          2A3
        R=Q**2.                                                         2A3
        S=F*R                                                           2A3
        T=.1*AL                                                         2A3
        XX=X/12.                                                        2A3
        WRITE (3,9) XX,S                                                2A3
        X=X+T                                                           2A3
        XY=X-AL                                                         2A3
        IF (XY) 2,3,3                                                   2A3
3       CONTINUE                                                        2A3
C       POD STRUCTURAL PROGRAM SCP=9                                    2A3
C       DEFLECTION AT TENTH-POINTS OF A BM FIXED AT                     2A3
C       ONE END AND SIMPLY SUPPORTED AT THE OTHER                       2A3
        X=.1*AL                                                         2A3
        WRITE (3,10)                                                    2A3
        WRITE (3,8)                                                     2A3
4       A=X**2.                                                         2A3
        B=X**3.                                                         2A3
        C=AL**3.                                                        2A3
        D=W*X                                                           2A3
        E=D/48.                                                         2A3
        G=E/E                                                           2A3
        R=G/AI                                                          2A3
        S=3.*AL                                                         2A3
        T=S*A                                                           2A3
        U=2.*B                                                          2A3
        V=T-U                                                           2A3
        Y=V-C                                                           2A3
        DEF=Y*R                                                         2A3
        DEF=0.-DEF                                                      2A3
        AR=.1*AL                                                        2A3
        XX=X/12.                                                        2A3
        WRITE (3,9) XX,DEF                                              2A3
        X=X+AR                                                          2A3
        XY=X-AL                                                         2A3
        IF (XY) 4,5,5                                                   2A3
5       CALL EXIT                                                       2A3
C                                                                       2A3
6       FORMAT (6F10.0)                                                 2A3
7       FORMAT (1H1,'FIXED-ENDBEAM')                                    2A3
8       FORMAT ('DISTANCE(FT)DEFLECTION(IN)')                           2A3
9       FORMAT (2F16.4)                                                 2A3
10      FORMAT (1H1,'ONEENDSIMPLYSUPPORTED')                            2A3
        END                                                             2A3
// DUP
*STORE      WS  UA  M2A3
```

| FIXED-END BEAM<br>DISTANCE(FT) | DEFLECTION(IN) |
|---|---|
| 4.00 | .03 |
| 8.00 | .10 |
| 12.00 | .18 |
| 16.00 | .24 |
| 20.00 | .26 |
| 24.00 | .24 |
| 28.00 | .18 |
| 32.00 | .10 |
| 36.00 | .03 |
| 40.00 | .00 |

ONE END SIMPLY SUPPORTED

| DISTANCE(FT) | DEFLECTION(IN) |
|---|---|
| 4.00 | .20 |
| 8.00 | .37 |
| 12.00 | .48 |
| 16.00 | .53 |
| 20.00 | .51 |
| 24.00 | .43 |
| 28.00 | .31 |
| 32.00 | .17 |
| 36.00 | .05 |
| 40.00 | .00 |

LISTING AND SAMPLE PROBLEM

FOR PROGRAM 2.B.1

CONCRETE FRAME ANALYSIS - PART I

```
// JOB 1
// FOR
*IOCS(CARD,1132PRINTER,DISK)
*LIST ALL
C       POP STRUCTURAL PROGRAM SUP-5-1                                          2B1
C       SHEAR AND MOMENT ANALYIS FOR 1-,2-, OR 3-CELL CONDUITS OR               2B1
C       CULVERTS COMPOSED OF UNIFORMLY LOADED PRISMATIC AND/OR HAUNCHED         2B1
C       MEMBERS, WITHOUT SIDESWAY - PART1.                                      2B1
        DIMENSION S(20), W(20), A(20), B(20), A1(20), DM(20), SK(20)            2B1
        DIMENSION COFA(20), COF(20), DF(20), SUM(20), BAL(20)                   2B1
1       DO 2 I=1,20                                                             2B1
C       IN THE FOLLOWING STATEMENT, THE SYMBOL S REPRESENTS THE CLEAR SPAN2B1
C       IN FEET, SK IS THE THICKNESS OF MEMBER IN FEET, COF IS THE HAUNCH 2B1
C       DEPTH IN FEET, A1 IS THE RELATIVE MOMENT OF INERTIA, BAL IS THE         2B1
C       DEPTH TO THE CENTER OF STEEL FROM TENSILE FACE, AND DM IS THE           2B1
C       SLOPE OF THE HAUNCH.                                                    2B1
2       READ (2,46) S(I),SK(I),COF(I),A1(I),DM(I),W(I),BAL(I)                   2B1
C       IN THE NEXT TWENTY STATEMENTS, THE SYMBOL DF REPRESENTS THE WIDTH 2B1
C       OF THE ADJACENT MEMBER AT POSITION I.  (I AS IN INDEX.)                 2B1
        DF(1)=SK(16)                                                            2B1
        DF(2)=SK(17)                                                            2B1
        DF(3)=SK(17)                                                            2B1
        DF(4)=SK(20)                                                            2B1
        DF(5)=SK(20)                                                            2B1
        DF(6)=SK(7)                                                             2B1
        DF(7)=SK(6)                                                             2B1
        DF(8)=SK(9)                                                             2B1
        DF(9)=SK(8)                                                             2B1
        DF(10)=SK(19)                                                           2B1
        DF(11)=SK(19)                                                           2B1
        DF(12)=SK(18)                                                           2B1
        DF(13)=SK(18)                                                           2B1
        DF(14)=SK(15)                                                           2B1
        DF(15)=SK(14)                                                           2B1
        DF(16)=SK(1)                                                            2B1
        DF(17)=SK(2)                                                            2B1
        DF(18)=SK(13)                                                           2B1
        DF(19)=SK(10)                                                           2B1
        DF(20)=SK(5)                                                            2B1
C       IN THE NEXT TWENTY STATEMENTS, THE SYMBOL COFA REPRESENTS THE           2B1
C       IN LENGTH OF THE HAUNCH IN FEET.                                        2B1
        COFA(1)=COF(16)                                                         2B1
        COFA(2)=COF(17)                                                         2B1
        COFA(3)=COF(17)                                                         2B1
        COFA(4)=COF(20)                                                         2B1
        COFA(5)=COF(20)                                                         2B1
        COFA(6)=COF(7)                                                          2B1
        COFA(7)=COF(6)                                                          2B1
        COFA(8)=COF(9)                                                          2B1
        COFA(9)=COF(8)                                                          2B1
        COFA(10)=COF(19)                                                        2B1
        COFA(11)=COF(19)                                                        2B1
        COFA(12)=COF(18)                                                        2B1
        COFA(13)=COF(18)                                                        2B1
        COFA(14)=COF(15)                                                        2B1
        COFA(15)=COF(14)                                                        2B1
        COFA(16)=COF(1)                                                         2B1
        COFA(17)=COF(2)                                                         2B1
        COFA(18)=COF(13)                                                        2B1
        COFA(19)=COF(10)                                                        2B1
        COFA(20)=COF(5)                                                         2B1
```

```
      DO 3 I=1,20                                                       2B1
3     A(I)=(SK(I)*DF(I)+DM(I)*COF(I)*COF(I))/(2.*SK(I))                 2B1
      DO 4 I=1,20                                                       2B1
4     WRITE (2,45) SK(I),COF(I),DF(I),A(I),,COFA(I),BAL(I)              2B1
      DO 5 L=1,20,2                                                     2B1
C     IN THE NEXT TWO STATEMENTS, THE SYMBOL S IS RE-DEFINED TO REPRESEN2B1
C     THE DISTANCE BETWEEN POINTS OF 1 - INFINITY.                      2B1
      S(L)=S(L)-A(L)-A(L+1)+((DF(L)+DF(L+1))/2.)                        2B1
5     S(L+1)=S(L)                                                       2B1
      DO 6 I=1,20                                                       2B1
      B(I)=A(I)/S(I)                                                    2B1
C     IN THE FOLLOWING STATEMENT, THE SYMBOL SK IS RE-DEFINED TO REPRESE2B1
C     STIFFNESS. HOPE YOU ARE WITH US, THERE IS WORSE TO COME.          2B1
6     SK(I)=(1.+12.*((.5+B(I))**2))*A1(I)/S(I)                          2B1
      DO 10 I=1,20                                                      2B1
      DO 7 L=1,21,2                                                     2B1
      IF (I-L) 9,8,7                                                    2B1
7     CONTINUE                                                          2B1
C     IN STATEMENTS IMMEDIATELY FOLLOWING, THE SYMBOL COF IS RE-DEFINED 2B1
C     TO REPRESENT THE CARRYOVER FACTOR, OF ALL THINGS.                 2B1
8     COF(I)=0.-(1.-12.*(.5+B(I))*(.5+B(I+1)))/(1.+12.*((.5+B(I))**2))  2B1
      GO TO 10                                                          2B1
9     COF(I)=0.-(1.-12.*(.5+B(I))*(.5+B(I-1)))/(1.+12.*((.5+B(I))**2))  2B1
10    CONTINUE                                                          2B1
      CTR=1.                                                            2B1
C     THE NEXT TWENTY CODED INSTRUCTIONS ARE EXECUTED THREE TIMES. ON   2B1
C     THE FIRST TRIP THROUGH (CTR = 1.), THE SYMBOL SK STILL REPRESENTS 2B1
C     STIFFNESS. ON THE SECOND TIME THROUGH (CTR = 0.), SK IS RE-DEFINED2B1
C     TO REPRESENT THE FIXED END MOMENT, AND DURING THE THIRD AND FINAL 2B1
C     RUN (CTR = 2.), IT IS AGAIN RE-DEFINED TO REPRESENT CARRYOVER.    2B1
11    SUM(1)=SK(1)+SK(18)                                               2B1
      SUM(2)=SK(2)+SK(3)+SK(17)                                         2B1
      SUM(3)=SUM(2)                                                     2B1
      SUM(4)=SK(4)+SK(5)+SK(20)                                         2B1
      SUM(5)=SUM(4)                                                     2B1
      SUM(6)=SK(6)+SK(7)                                                2B1
      SUM(7)=SUM(6)                                                     2B1
      SUM(8)=SK(8)+SK(9)                                                2B1
      SUM(9)=SUM(8)                                                     2B1
      SUM(10)=SK(10)+SK(11)+SK(19)                                      2B1
      SUM(11)=SUM(10)                                                   2B1
      SUM(12)=SK(12)+SK(13)+SK(16)                                      2B1
      SUM(13)=SUM(12)                                                   2B1
      SUM(14)=SK(14)+SK(15)                                             2B1
      SUM(15)=SUM(14)                                                   2B1
      SUM(16)=SUM(1)                                                    2B1
      SUM(17)=SUM(2)                                                    2B1
      SUM(18)=SUM(12)                                                   2B1
      SUM(19)=SUM(10)                                                   2B1
      SUM(20)=SUM(4)                                                    2B1
      IF (CTR-1.) 17,12,24                                              2B1
12    DO 15 I=1,20                                                      2B1
      IF (SUM(I)) 14,13,14                                              2B1
C     IN STATEMENTS 207 AND 208 DF IS THE DISTRIBUTION FACTOR.0         2B1
13    DF(I)=0.                                                          2B1
      GO TO 15                                                          2B1
14    DF(I)=SK(I)/SUM(I)                                                2B1
C     THE NEXT STATEMENT IS WHERE SK BECOMES FEM.                       2B1
15    SK(I)=W(I)*S(I)*S(I)*(1.+6.*B(I)+6.*B(I)*B(I))/12.                2B1
      WRITE (3,48)                                                      2B1
      DO 16 I=1,20                                                      2B1
16    WRITE (3,49) SK(I),A(I),DF(I),COF(I)                              2B1
```

```
      CTR=0.                                                            2B1
      GO TO 11                                                          2B1
17    DO 18 I=1,20                                                      2B1
C     IN THE NEXT STATEMENTS, BAL REPRESENTS BALANCE AND DM IS THE      2B1
C     DISTRIBUTED MOMENT. ALL RATHER CONFUSING, BUT NECESSARY.          2B1
      BAL(I)=DF(I)*(0.-SUM(I))                                          2B1
18    DM(I)=SK(I)+BAL(I)                                                2B1
19    DO 25 I=1,20                                                      2B1
      DO 25 L=1,21,2                                                    2B1
      IF (I-L) 22,21,20                                                 2B1
20    CONTINUE                                                          2B1
C     THE NEXT STATEMENT IS WHERE SK BECOMES CARRYOVER.                 2B1
21    SK(I)=BAL(I+1)*COF(I+1)                                           2B1
      GO TO 23                                                          2B1
22    SK(I)=BAL(I-1)*COF(I-1)                                           2B1
23    CONTINUE                                                          2B1
      CTR=2.                                                            2B1
      GO TO 11                                                          2B1
24    DO 25 I=1,20                                                      2B1
      BAL(I)=DF(I)*(0.-SUM(I))                                          2B1
25    DM(I)=DM(I)+SK(I)+BAL(I)                                          2B1
      DIFFM=0.                                                          2B1
      DO 36 I=1,20                                                      2B1
      IF (DM(I)) 26,27,27                                               2B1
26    Z=0.-DM(I)                                                        2B1
      GO TO 28                                                          2B1
27    Z=DM(I)                                                           2B1
28    IF (SK(I)) 29,30,30                                               2B1
29    X=0.-SK(I)                                                        2B1
      GO TO 31                                                          2B1
30    X=SK(I)                                                           2B1
31    IF (BAL(I)) 32,33,33                                              2B1
32    Y=0.-BAL(I)                                                       2B1
      GO TO 34                                                          2B1
33    Y=BAL(I)                                                          2B1
34    DIFF=X-Y                                                          2B1
      IF (DIFF) 35,36,36                                                2B1
35    DIFF=0.-DIFF                                                      2B1
36    EDIFF=DIFF-.0005*Z                                                2B1
      IF (DIFFM-EDIFF) 37,37,38                                         2B1
37    DIFFM=EDIFF                                                       2B1
38    CONTINUE                                                          2B1
      IF (DIFFM) 39,39,19                                               2B1
39    WRITE (3,50)                                                      2B1
      DO 40 I=1,20,2                                                    2B1
C     IN THE NEXT TWO STATEMENTS, S IS RE-DEFINED TO REPRESENT THE      2B1
C     DISTANCE BETWEEN CENTERLINES OF MEMBERS.                          2B1
      S(I)=S(I)+A(I)+A(I+1)                                             2B1
40    S(I+1)=S(I)                                                       2B1
      DO 44 I=1,20                                                      2B1
      IF (W(I)) 41,42,42                                                2B1
41    W(I)=0.-W(I)                                                      2B1
42    WRITE (3,51) DM(I)                                                2B1
      IF (DM(I)) 43,44,44                                               2B1
43    DM(I)=0.-DM(I)                                                    2B1
44    WRITE (2,47) S(I),DM(I),W(I)                                      2B1
      CALL EXIT                                                         2B1
C                                                                       2B1
45    FORMAT (F7.3,F7.4,F7.3,F6.3,F7.4,F5.3)                            2B1
46    FORMAT (F6.3,F5.3,F6.4,F5.2,F6.4,F7.3,F4.3)                       2B1
47    FORMAT (F7.3,F9.3,F7.3)                                           2B1
48    FORMAT (13X3HFEM9X1HA9X2HDF7X3HCOF/)                              2B1
```

```
49      FORMAT (F19.5,F10.5,F10.4,F10.4)                                ZB1
50      FORMAT (/12X2HDM/)                                              ZB1
51      FORMAT (F17.5)                                                  ZB1
        END                                                             ZB1
// DUP
*STORE        WS  UA  M2B1
// XQT M2B1
```

| FEM | A | DF | COF |
|---|---|---|---|
| 916.644 | 3.190 | .5000 | .8154 |
| -916.644 | 3.190 | .3333 | .8154 |
| 916.644 | 3.190 | .3333 | .8154 |
| -916.644 | 3.190 | .3333 | .8154 |
| 916.644 | 3.190 | .3333 | .8154 |
| -916.644 | 3.190 | .5000 | .8154 |
| 305.548 | 3.190 | .5000 | .8154 |
| -305.548 | 3.190 | .5000 | .8154 |
| 916.644 | 3.190 | .5000 | .8154 |
| -916.644 | 3.190 | .3333 | .8154 |
| 916.644 | 3.190 | .3333 | .8154 |
| -916.644 | 3.190 | .3333 | .8154 |
| 916.644 | 3.190 | .3333 | .8154 |
| -916.644 | 3.190 | .5000 | .8154 |
| 305.548 | 3.190 | .5000 | .8154 |
| -305.548 | 3.190 | .5000 | .8154 |
| .000 | 3.190 | .3333 | .8154 |
| .000 | 3.190 | .3333 | .8154 |
| .000 | 3.190 | .3333 | .8154 |
| .000 | 3.190 | .3333 | .8154 |

| DM |
|---|
| 466.934 |
| -1108.859 |
| 1012.751 |
| -1012.751 |
| 1108.859 |
| -466.934 |
| 466.934 |
| -466.934 |
| 466.934 |
| -1108.859 |
| 1012.751 |
| -1012.751 |
| 1108.859 |
| -466.934 |
| 466.934 |
| -466.934 |
| 96.108 |
| -96.108 |
| 96.108 |
| -96.108 |

LISTING AND SAMPLE OUTPUT

FOR PROGRAM 2.B.2

CONCRETE FRAME ANALYSIS - PART II

```
// JOB 1
// FOR
*IOCS(CARD,1132PRINTER,DISK)
*LIST ALL
C       SHEAR AND MOMENT ANALYSIS FOR 1-, 2-, OR 3-CELL CONDUITS OR        2B2
C       CULVERTS COMPOSED OF UNIFORMLY LOADED PRISMATIC AND/OR HAUNCHED    2B2
C       MEMBERS, WITHOUT SIDEWAY - PART 2.                                 2B2
        DIMENSION S(20), A(20), T(20), COF(20), DM(20), DF(20), W(20)      2B2
        DIMENSION V(20), VF(20), VA(20), C(20), COFA(20)                   2B2
1       DO 2 I=1,20                                                        2B2
2       READ (2,29) T(I),COF(I),DF(I),A(I),COFA(I),C(I)                    2B2
        DO 3 I=1,20                                                        2B2
3       READ (2,30) S(I),DM(I),W(I)                                        2B2
        DO 4 I=1,20,2                                                      2B2
C       IN THE NEXT STATEMENT, VA REPRESENTS THE DIFFERENCE BETWEEN        2B2
C       MOMENTS AT OPPOSITE ENDS OF MEMBER.                                2B2
        VA(I)=DM(I)-DM(I+1)                                                2B2
        V(I)=W(I)*S(I)/2.+(VA(I)/S(I))                                     2B2
4       V(I+1)=W(I)*S(I)/2.-(VA(I)/S(I))                                   2B2
        CALL DATSW (1,NSS1)                                                2B2
        GO TO (5,6), NSS1                                                  2B2
5       WRITE (3,31)                                                       2B2
        GO TO 7                                                            2B2
6       WRITE (3,35)                                                       2B2
7       DO 14 I=1,20                                                       2B2
        WRITE (2,37) DM(I),DF(I),A(I),COFA(I),W(I),C(I),T(I),S(I)          2B2
C       IN THE FIVE STATMENTS FOLLOWING, T REPRESENTS DEPTH TO THE         2B2
C       CENTER OF STEEL, C REPRESENTS SHEAR AT END OF HAUNCH,              2B2
C       VF REPRESENTS SHEAR AT FACE, VA REPRESENTS SHEAR AT POINT OF       2B2
C       INFINITE I, AND A REPRESENTS SHEAR BETWEEN VA AND SHEAR AT END OF  2B2
C       THE HAUNCH.  (CALLED VAEM DURING PRINT-OUT.)                       2B2
        T(I)=T(I)-C(I)                                                     2B2
        VF(I)=V(I)-(W(I)*DF(I)/2.)                                         2B2
        VA(I)=V(I)-(W(I)*A(I))                                             2B2
        C(I)=V(I)-(W(I)*((DF(I)/2.)+COFA(I)))                              2B2
        A(I)=(VA(I)+C(I))/2.                                               2B2
        IF (W(I)) 8,10,8                                                   2B2
C       IN THE FOLLOWING STATEMENT, S REPRESENTS THE QUANTITY UNDER RADICA2B2
C       OF THE QUADRATIC EQUATION.                                         2B2
8       S(I)=V(I)**2-(2.*DM(I)*W(I))                                       2B2
        IF (S(I)) 10,9,9                                                   2B2
C       IN THE NEXT STATEMENT, S BECOMES THE DISTANCE TO ZERO MOMENT.      2B2
9       S(I)=(V(I)-SQRT(S(I)))/W(I)                                        2B2
C       DM NOW BECOMES VPC (SHEAR AT POINT OF CONTRAFLEXURE).              2B2
        DM(I)=V(I)-(W(I)*S(I))                                             2B2
        GO TO 11                                                           2B2
10      S(I)=0.                                                            2B2
        DM(I)=0.                                                           2B2
11      WRITE (2,36) V(I),VF(I),VA(I),C(I),S(I)                            2B2
        CALL DATSW (1,NSS1)                                                2B2
        GO TO (12,13), NSS1                                                2B2
12      WRITE (3,32) V(I),VF(I),DM(I)                                      2B2
        GO TO 14                                                           2B2
13      WRITE (3,34) V(I),VA(I),A(I),C(I),DM(I)                            2B2
C       IN THE NEXT STATEMENT, V BECOMES DISTANCE TO ZERO MOMENT.          2B2
14      V(I)=S(I)                                                          2B2
        CALL DATSW (2,NSS2)                                                2B2
        GO TO (26,15), NSS2                                                2B2
15      CALL DATSW (1,NSS1)                                                2B2
        GO TO (16,17), NSS1                                                2B2
16      WRITE (3,35)                                                       2B2
        GO TO 18                                                           2B2
```

```
17      WRITE (3,39)                                                    2B2
18      DO 27 I=1,20                                                    2B2
C       IN THE NEXT TWO STATEMENTS, S BECOMES DEPTH TO CENTER OF STEEL  2B2
C       AT FACE, AND VF BECOMES UNIT SHEAR AT D/2 FROM FACE.            2B2
        S(I)=T(I)+COF(I)                                                2B2
        VF(I)=(VF(I)-W(I)*S(I)/2.)/(S(I)*144.)                          2B2
C       IN THE NEXT FOUR STATEMENTS, S IS RE-DEFINED TO REPRESENT DEPTH 2B2
C       TO CENTER OF STEEL AT POINT OF INFINITE I, VA BECOMES USA,      2B2
C       THE SYMBOL A BECOMES USACH, C BECOMES USECH, AND WE ARE GETTING 2B2
C       PRETTY MIXED UP OURSELVES.                                      2B2
        S(I)=T(I)+(COF(I)*(1.-(COF(I)/(T(I)*2.))))                      2B2
        VA(I)=VA(I)/(144.*S(I))                                         2B2
        A(I)=A(I)*2./((T(I)+S(I))*144.)                                 2B2
        C(I)=C(I)/(144.*(T(I)))                                         2B2
C       THE NEXT S REPRESENTS HALF THE WIDTH OF ADJACENT MEMBER.        2B2
        S(I)=DF(I)/2.                                                   2B2
        IF (V(I)-S(I)) 19,19,20                                         2B2
19      DM(I)=0.                                                        2B2
        GO TO 24                                                        2B2
C       THE NEXT S BECOMES THE DIFFERENCE BETWEEN DISTANCE TO ZERO MOMENT 2B2
C       AND PREVIOUSLY RE-DEFINED S, IN CASE YOU ARE STILL READING.     2B2
20      S(I)=V(I)-S(I)                                                  2B2
        IF (COFA(I)-S(I)) 22,22,21                                      2B2
C       THE NEXT S IS NOTHING MORE THAN PARTIAL HAUNCH DEPTH.           2B2
21      S(I)=(COFA(I)-V(I)+(DF(I)*.5))*COF(I)/COFA(I)                   2B2
C       THE NEXT S, HOWEVER, BECOMES DEPTH TO STEEL AT P.C. WITHIN THE  2B2
C       HAUNCH, AND THE ONE AFTER THAT BECOMES THE DEPTH TO STEEL OUT-  2B2
C       SIDE THE HAUNCH AT P.C., BUT FORTUNATELY NONE OF THE OTHER      2B2
C       VARIABLES ARE MAKING PASSES OF THEMSELVES.                      2B2
        S(I)=T(I)+S(I)                                                  2B2
        GO TO 23                                                        2B2
22      S(I)=T(I)                                                       2B2
23      DM(I)=DM(I)/(144.*S(I))                                         2B2
24      CALL DATSW (1,NSS1)                                             2B2
        GO TO (25,26), NSS1                                             2B2
25      WRITE (3,36) VF(I),DM(I)                                        2B2
        GO TO 27                                                        2B2
26      WRITE (3,40) VA(I),A(I),C(I),DM(I)                              2B2
27      CONTINUE                                                        2B2
        GO TO 1                                                         2B2
28      CONTINUE                                                        2B2
C                                                                       2B2
29      FORMAT (F7.3,F7.4,F7.3,F6.3,F7.4,F5.3)                          2B2
30      FORMAT (F7.3,F9.3,F7.3)                                         2B2
31      FORMAT (25X1HV10X2HVF10X3HVPC/)                                 2B2
32      FORMAT (F29.3,F12.3,F12.3)                                      2B2
33      FORMAT (15X1HV10X2HVA9X4HVAEH9X3HVEH9X3HVPC/)                   2B2
34      FORMAT (F17.3,F12.3,F12.3,F12.3,F12.3)                          2B2
35      FORMAT (/29X5HUSU2F6X4HUSPC/)                                   2B2
36      FORMAT (F34.3,F10.3)                                            2B2
37      FORMAT (F9.3,F7.3,F6.3,F7.4,F7.3,F5.3,F7.3,F7.3)                2B2
38      FORMAT (F9.3,F9.3,F9.3,F9.3,F7.3)                               2B2
39      FORMAT (/20X3HUSA6X5HUSAEH6X4HUSEH6X4HUSPC/)                    2B2
40      FORMAT (F24.3,F10.3,F10.3,F10.3)                                2B2
        END                                                             2B2
// DUP
*STORE       WS  UA  M2B2
// XQT M2B2
```

| V | VA | VAEH | VEH | VPC |
|---|---|---|---|---|
| 241.378 | 113.140 | 73.593 | 34.046 | 143.950 |
| 331.472 | 203.234 | 163.688 | 124.141 | 143.950 |
| 266.425 | 158.187 | 118.640 | 79.093 | 24.781 |
| 266.425 | 158.187 | 118.640 | 79.093 | 24.781 |
| 331.472 | 203.234 | 163.688 | 124.141 | 143.950 |
| 241.378 | 113.140 | 73.593 | 34.046 | 143.950 |
| 95.475 | 52.729 | 39.547 | 26.365 | .000 |
| 95.475 | 52.729 | 39.547 | 26.365 | .000 |
| 241.378 | 113.140 | 73.593 | 34.046 | 143.950 |
| 331.472 | 203.234 | 163.688 | 124.141 | 143.950 |
| 266.425 | 158.187 | 118.640 | 79.093 | 24.781 |
| 266.425 | 158.187 | 118.640 | 79.093 | 24.781 |
| 331.472 | 203.234 | 163.688 | 124.141 | 143.950 |
| 241.378 | 113.140 | 73.593 | 34.046 | 143.950 |
| 95.475 | 52.729 | 39.547 | 26.365 | .000 |
| 95.475 | 52.729 | 39.547 | 26.365 | .000 |
| .000 | .000 | .000 | .000 | .000 |
| .000 | .000 | .000 | .000 | .000 |
| .000 | .000 | .000 | .000 | .000 |
| .000 | .000 | .000 | .000 | .000 |

| USA | USAEH | USEH | USPC |
|---|---|---|---|
| .124 | .095 | .054 | .140 |
| .223 | .212 | .195 | .204 |
| .174 | .153 | .124 | .039 |
| .174 | .153 | .124 | .039 |
| .223 | .212 | .195 | .204 |
| .124 | .095 | .054 | .140 |
| .058 | .051 | .041 | .000 |
| .058 | .051 | .041 | .000 |
| .124 | .095 | .054 | .140 |
| .223 | .212 | .195 | .204 |
| .174 | .153 | .124 | .039 |
| .174 | .153 | .124 | .039 |
| .223 | .212 | .195 | .204 |
| .124 | .095 | .054 | .140 |
| .058 | .051 | .041 | .000 |
| .058 | .051 | .041 | .000 |
| .000 | .000 | .000 | .000 |
| .000 | .000 | .000 | .000 |
| .000 | .000 | .000 | .000 |
| .000 | .000 | .000 | .000 |

LISTING AND SAMPLE OUTPUT

FOR PROGRAM 2.B.3

CONCRETE FRAME ANALYSIS - PART III

```
// JOB 1
// FOR
*IOCS(CARD,1132PRINTER,DISK)
*LIST ALL
C     POD STRUCTURAL PROGRAM SCP-5-3                                          2B3
C     SHEAR AND MOMENT ANALYSIS FOR 1-, 2-, OR 3-CELL CONDUITS OR             2B3
C     CULVERTS COMPOSED OF UNIFORMLY LOADED PRISMATIC AND/OR HAUNCHED         2B3
C     MEMBERS, WITHOUT SIDESWAY - PART 3.                                     2B3
      DIMENSION DM(20), XF(20), A(20), XEH(20), W(20), C(20), XMPOS(20),2B3
     1 S(20)                                                                  2B3
      DIMENSION V(20), VF(20), VA(20), VEH(20), XMZER(20), I(20)              2B3
1     DO 4 I=1,20                                                             2B3
C     XF NOW BECOMES DISTANCE TO FACE, AND XEH BECOMES                        2B3
      READ (2,21) DM(I),XF(I),A(I),XEH(I),W(I),C(I),I(I),S(I)                 2B3
      READ (2,22) V(I),VF(I),VA(I),VEH(I),XMZER(I)                            2B3
C     DISTANCE TO END OF HAUNCH.                                              2B3
      XF(I)=XF(I)/2.                                                          2B3
      XEH(I)=XF(I)+XEH(I)                                                     2B3
      IF (W(I)) 2,3,2                                                         2B3
2     XMPOS(I)=V(I)/W(I)                                                      2B3
      GO TO 4                                                                 2B3
3     XMPOS(I)=0.                                                             2B3
4     CONTINUE                                                                2B3
      CALL DATSW (1,NSS1)                                                     2B3
      GO TO (5,6), NSS1                                                       2B3
5     WRITE (3,27)                                                            2B3
      GO TO 7                                                                 2B3
6     WRITE (3,23)                                                            2B3
7     DO 11 I=1,20                                                            2B3
      CALL DATSW (1,NSS1)                                                     2B3
      GO TO (8,9), NSS1                                                       2B3
8     WRITE (3,26) S(I),XF(I),XMZER(I),XMPOS(I)                               2B3
      GO TO 10                                                                2B3
9     WRITE (3,24) S(I),XF(I),A(I),XEH(I),XMZER(I),XMPOS(I)                   2B3
C     IN THE NEXT FOUR STATEMENTS, VF REPRESENTS MOMENT CORRECTION,           2B3
C     XF REPRESENTS MOMENT AT FACE, A REPRESENTS MOMENT AT A,                 2B3
C     AND XEH REPRESENTS MOMENT AT END OF HAUNCH.                             2B3
10    VF(I)=XF(I)*(V(I)+VF(I))/6.                                             2B3
      XF(I)=DM(I)-VF(I)*3.                                                    2B3
      A(I)=DM(I)-(((V(I)+VA(I))/2.)*A(I))                                     2B3
11    XEH(I)=DM(I)-(((V(I)+VEH(I))/2.)*XEH(I))                                2B3
      DO 14 I=1,20,2                                                          2B3
      IF (W(I)) 12,13,12                                                      2B3
C     FROM HERE ON OUT, XMPOS REPRESENTS DISTANCE TO MAX POSITIVE MOMENT      2B3
12    XMPOS(I)=DM(I)-((V(I)*V(I))/(2.*W(I)))                                  2B3
      GO TO 14                                                                2B3
13    XMPOS(I)=0.                                                             2B3
14    XMPOS(I+1)=XMPOS(I)                                                     2B3
      CALL DATSW (1,NSS1)                                                     2B3
      GO TO (15,16), NSS1                                                     2B3
15    WRITE (3,29)                                                            2B3
      GO TO 17                                                                2B3
16    WRITE (3,25)                                                            2B3
17    DO 20 I=1,20                                                            2B3
      CALL DATSW (1,NSS1)                                                     2B3
      GO TO (18,19), NSS1                                                     2B3
18    WRITE (3,30) DM(I),XF(I),XMPOS(I),VF(I)                                 2B3
      GO TO 20                                                                2B3
19    WRITE (3,26) DM(I),XF(I),A(I),XEH(I),XMPOS(I),VF(I)                     2B3
20    CONTINUE                                                                2B3
      GO TO 1                                                                 2B3
C                                                                             2B3
```

```
21      FORMAT (F9.3,F7.3,F6.3,F7.4,F7.3,F5.3,F7.3,F7.3)                    2B3
22      FORMAT (F9.3,F9.3,F9.3,F9.3,F7.3)                                   2B3
23      FORMAT (1X1H59X2HXF6X1HA9X3HXE16X5HXM2ERX5X5HXMPOS/)                2B3
24      FORMAT (F15.3,F10.3,F10.3,F10.3,F10.3,F10.3)                        2B3
25      FORMAT (/11X2HDM9X3HDMF8X3HDMA8X4HDMEB6X5HDMPOS6X5HDMCOR/)          2B3
26      FORMAT (F16.3,F11.3,F11.3,F11.3,F11.3,F11.3)                        2B3
27      FORMAT (21X1H59X2HXF7X5HXM2ERX5X5HXMPOS/)                           2B3
28      FORMAT (F25.3,F10.3,F10.3,F10.3)                                    2B3
29      FORMAT (/14X2HDM10X3HDMF8X5HDMPOS7X5HDMCOR/)                        2B3
30      FORMAT (F19.3,F12.3,F12.3,F12.3)                                    2B3
        END                                                                 2B3
// DUP
*STORE        WS  UA  M2B3
// XQT M2B3
```

| S | XF | A | XEH | XMZER | XMPOS |
|---|---|---|---|---|---|
| 14.250 | 2.375 | 3.190 | 5.157 | 2.424 | 6.004 |
| 14.250 | 2.375 | 3.190 | 5.157 | 4.665 | 8.246 |
| 14.250 | 2.375 | 3.190 | 5.157 | 6.509 | 7.125 |
| 14.250 | 2.375 | 3.190 | 5.157 | 6.509 | 7.125 |
| 14.250 | 2.375 | 3.190 | 5.157 | 4.665 | 8.246 |
| 14.250 | 2.375 | 3.190 | 5.157 | 2.424 | 6.004 |
| 14.250 | 2.375 | 3.190 | 5.157 | .000 | 7.125 |
| 14.250 | 2.375 | 3.190 | 5.157 | .000 | 7.125 |
| 14.250 | 2.375 | 3.190 | 5.157 | 2.424 | 6.004 |
| 14.250 | 2.375 | 3.190 | 5.157 | 4.665 | 8.246 |
| 14.250 | 2.375 | 3.190 | 5.157 | 6.509 | 7.125 |
| 14.250 | 2.375 | 3.190 | 5.157 | 6.509 | 7.125 |
| 14.250 | 2.375 | 3.190 | 5.157 | 4.665 | 8.246 |
| 14.250 | 2.375 | 3.190 | 5.157 | 2.424 | 6.004 |
| 14.250 | 2.375 | 3.190 | 5.157 | .000 | 7.125 |
| 14.250 | 2.375 | 3.190 | 5.157 | .000 | 7.125 |
| 14.250 | 2.375 | 3.190 | 5.157 | .000 | .000 |
| 14.250 | 2.375 | 3.190 | 5.157 | .000 | .000 |
| 14.250 | 2.375 | 3.190 | 5.157 | .000 | .000 |
| 14.250 | 2.375 | 3.190 | 5.157 | .000 | .000 |

| DM | DMF | DMA | DMEH | DMPOS | DMCOR |
|---|---|---|---|---|---|
| 466.934 | 7.038 | -98.522 | -243.316 | -257.734 | 153.299 |
| 1108.859 | 434.990 | 256.003 | -66.053 | -257.734 | 224.623 |
| 1012.751 | 445.868 | 303.595 | 70.171 | -7.638 | 188.961 |
| 1012.751 | 445.868 | 303.595 | 70.171 | -7.638 | 188.961 |
| 1108.859 | 434.990 | 256.003 | -66.053 | -257.729 | 224.623 |
| 466.934 | 7.038 | -98.522 | -243.316 | -257.729 | 153.299 |
| 466.934 | 277.973 | 230.549 | 152.739 | 126.804 | 62.987 |
| 466.934 | 277.973 | 230.549 | 152.739 | 126.804 | 62.987 |
| 466.934 | 7.038 | -98.522 | -243.316 | -257.734 | 153.299 |
| 1108.859 | 434.990 | 256.003 | -66.053 | -257.734 | 224.623 |
| 1012.751 | 445.868 | 303.595 | 70.171 | -7.638 | 188.961 |
| 1012.751 | 445.868 | 303.595 | 70.171 | -7.638 | 188.961 |
| 1108.859 | 434.990 | 256.003 | -66.053 | -257.729 | 224.623 |
| 466.934 | 7.038 | -98.522 | -243.316 | -257.729 | 153.299 |
| 466.934 | 277.973 | 230.549 | 152.739 | 126.804 | 62.987 |
| 466.934 | 277.973 | 230.549 | 152.739 | 126.804 | 62.987 |
| 96.108 | 96.108 | 96.108 | 96.108 | .000 | .000 |
| 96.108 | 96.108 | 96.108 | 96.108 | .000 | .000 |
| 96.108 | 96.108 | 96.108 | 96.108 | .000 | .000 |
| 96.108 | 96.108 | 96.108 | 96.108 | .000 | .000 |

## ACKNOWLEDGEMENT


| PROGRAM | ORIGINATOR |
| --- | --- |
| 2.B.1<br>2.B.2<br>2.B.3 | J.J. Miller and<br>H.H. Sharp, U.S.<br>Army Corp of Engineers<br>P.O. Box 1538<br>Albuquerque, New Mexico |